

# C6 Raffinate

## Description

Fuel additive

## Application

Fuel Additive

Properties	Condition	Method	Unit	C6 Raffinate
Appearance		Visual		Bright & Clear
Benzene		Gas Chro	wt %	Max 0.2
Copper Corrosion	at 50°C,3hrs	ASTM D-130		Max 1
Distillation - End Point		ASTM D 86	°C	Max 190
Doctor Test		ASTM D-235		Negative
H2O		DEW POINT METER	vol.ppm	Max 0.1
H2S		UOP 163	wt ppm	Max 1
Olefin		Gas Chro	wt %	Max 10
Oxidation Stability		ASTM D 7525	min	Min 480
RSH(T-S)		ASTM D-5453	wt ppm	Max 5
Reid Vapor Pressure	37.8 °C	ASTM D 323	kg/cm <sup>2</sup>	Max 0.5

Issued Date : 2021-12-23

The information contained herein, including, but not limited to, data, statements and typical values, are given in good faith. LG Chem makes no warranty or guarantee, expressed or implied, (i) that the result described herein will be obtained under end - use conditions, or (ii) as to the effectiveness or safety of any design incorporating LG Chem materials, products, recommendations or advice. Further, any information contained herein shall not be construed as a part of legally binding offer. Especially, the typical values should be regarded as reference values only and not as binding minimum values. Each user bear full responsibility for making its own determination as to the suitability of LG Chem's materials, products, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating LG Chem material or products will be safe and suitable for use under end - use conditions. The data contained herein can be changed without notice as a result of the quality improvement of the products.